



FEATURES

- The ZTM230 is a 230 VAC, 50 Hz, RF Wall Transmitter with 3 way capability. This Wall Transmitter can be controlled manually with the ZTH200 Z-Wave RF Remote Control, or the ACT multilevel auxiliary switch (AS200).
- The ZTM230 is a dual switch design, where each switch will serve as an individual RF transmitter and multiple switch taps will control lights "associated". "Association" adds control of Z-Wave devices to the wall transmitters.
- Only requires power and provides expanded lighting control when installed.
- Each ZTM230 Wall Mounted Transmitter also functions as an automatic repeater to other HomePro Modules to guarantee full home coverage of the RF signal.



APPLICATIONS

SAFETY AND SECURITY

- **Control Outside Lighting or Key Interior Lighting with One Touch** - With a ZTM230 Wall Mounted Transmitter you control the ON/OFF and DIM/BRIGHT of up to 5 loads at a time with one touch of the switch. Two and Three taps on the Transmitters right switch can control two additional groups of 5 loads.

COMFORT AND CONVENIENCE

- **Wall Mounted Transmitters** can be located in various parts of the home to operate different groupings of lights.

PRODUCT DESCRIPTION

This ZTM230 Wall Mounted Transmitter can be installed like a wall switch, however it does not directly connect to a load. Instead, it controls other Z-Wave devices (or nodes) that operate the ON/OFF or DIM/BRIGHT of lighting or other electrical loads.

The ZTM230 Wall Mounted Transmitter is identified to the network using a Controller. The ZTM230 has no load control capability, but instead control associated Z-Wave devices.

Subsequent configuring of the ZTM230 Wall Mounted Transmitter using the Controller allows it to operate the ON/OFF and DIM/BRIGHT of

associated groups of receivers by using multiple taps on the Transmitter switch. Up to 3 groups of (up to) 5 receivers per group can be controlled.

Groups programmed on the ZTM230 can only be controlled from the ZTM230, however any node in any of the groups can be controlled from any other controller or transmitter in the system singly or within another group.

HomePro products utilize radio frequency (RF) Z-Wave™ technology to communicate and inter-operate, and are compatible with other Z-Wave™ enabled RF products. See specifications of your Controller for details on programming.

ORDERING INFORMATION

Specify: **ZTM230W** - Wall Mounted Transmitter, Dual Switch, 230 VAC (White)

SPECIFICATIONS

Electrical

| | |
|--------------------|---|
| Power | 230 VAC +/- 10%, 50Hz supply. |
| Signal (Frequency) | 868.42 MHz |
| Range | Up to 30 meters line of sight between the Wireless Controller and the closest Z-Wave Receiver, however, all receivers relay the signal to the next closest receiver creating an RF network. |

Mechanical

| | |
|-------------|---|
| Dimensions | 82mm (W) x 82mm (L) x 48mm (D). |
| Weight | Approximately 142g (5.0 oz). |
| Mounting | The body of the unit is designed to fit inside any standard European electrical box, the depth of the back shell behind the metal mounting plate is 33.15mm. The retaining ring holds the provided Trim ring in place. Press-in installation occurs after Trim ring is in place. These products can be multiple ganged. |
| Connections | Four Position Terminal Block connections: L: Line Voltage N: Line Neutral 2: 3-Way reference (Neutral) 3: Three Way input from AS200. |

Environmental

| | |
|-----------------------------|------------------------------------|
| Operating Temperature Range | 32-105°F (0-40°C). Indoor use only |
| Humidity Range: | 10 to 95% non-condensing. |

Specifications may change without notice to improve product performance.



The product is compatible with other Z-Wave[®] enabled products